

## **An Appropriate Construction Noise Impact Criterion?**

Weixiong Wu, Ph.D. AKRF, Inc. 440 Park Avenue New York, NY 10016




#### **Background**

- Large-Scale Construction Projects In New York City
- Noise Impacts Caused by Construction Activities
- No Standardized Criteria for Construction Noise
- Construction Noise Assessment Procedure by City Environmental Quality Review (CEQR) Methodology
- Baseline Leq $(1) \ge 62 \text{ dBA} + 3 \text{ dBA} \text{Noise Criterion}$
- An Appropriate Noise Criterion?



### **Yankee Stadium Redevelopment**





### **Atlantic Yards Development**





### **First Avenue Properties Development**





## Columbia University Manhattanville Academic Mixed Use Development





#### **Construction Noise Analyses**

- Construction Operation Restrictions
  - Construction equipment must meet both EPA noise emission standards and new City Noise Code
  - Weekdays between 7:00 am and 6:00 pm
  - Alternative noise mitigation plan (July 1, 2007)
- CEQR Impact Criteria
  - Baseline Leq $(1) \le 60 \text{ dBA} + 5 \text{ dBA}$
  - Baseline Leq(1) = 61 dBA + 4 dBA
  - Baseline Leq $(1) \ge 62 \text{ dBA} + 3 \text{ dBA}$
- Impact Definition
  - Construction noise levels exceed the CEQR Criteria for a long period of time (two-year or longer)



### Noise Criteria (Residential)

#### No Standardized Federal Criteria for Construction Noise!

Sources	Descriptor	Absolute Level	Substantial Increase	
HUD	Ldn	65 dBA		
FTA	Leq(8)	80/70 dBA (Day/Night)		
FHWA	Leq(1)	67 dBA		
NYDOT	Leq	85 dBA for NYC		
NJDOT	Leq(1)		Baseline + 10 dBA	
California DOT	Leq(1)		Baseline + 12 dBA	
Connecticut DOT	L10(1)		Baseline + 15 dBA	
NYSDEC	Leq(1)		Baseline + 6 dBA	
New York City CEQR	Leq(1)		Baseline + 3 dBA (if Baseline ≥62 dBA)	



# FHWA Roadway Construction Noise Model User's Guide

Lot-Line Cons	truction Noise Criteria Limits A  Daytime (7 AM - 6 PM)		A-weighted in dB, RMS slow Evening (6 PM - 10 PM)		Nighttime (10 PM - 7 AM)	
Receptor Locations and Land- Uses	$\mathbf{L_{10}}$	L <sub>max</sub>	$\mathbf{L_{10}}$	L <sub>max</sub>	$\mathbf{L_{10}}$	L <sub>max</sub>
Noise- Sensitive Locations: (Residences, Institutions, Hotels, etc.)	75 or Baseline + 5 (whichever is louder)	85 90 (impact)	Baseline + 5	85	Baseline + 5 > (if Baseline <70) >Baseline + 3 (if Baseline 70)	80
Commercial Areas: (Businesses, Offices, Stores, etc.)	80 or Baseline + 5	None	None	None	None	None
Industrial Areas: (Factories, Plants, etc.)	85 or Baseline + 5	None	None	None	None	None



### **Average Ability to Perceive Changes in Noise Levels**

Change (dBA)	Human Perception of Sound
2-3	Barely perceptible
5	Readily noticeable
10	A doubling or halving of the loudness of sound
20	A "dramatic change"
40	Difference between a faintly audible sound and a very loud sound

Source: Bolt Beranek and Neuman, Inc., *Fundamentals and Abatement of Highway Traffic Noise*, Report No. PB-222-703. Prepared for Federal Highway Administration, June 1973.



### **Community Response to Increases in Noise Levels**

Change (dBA)	Category	Description
0	None	No observed reaction
5	Little	Sporadic complaints
10	Medium	Widespread complaints
15	Strong	Threats of community action
20	Very Strong	Vigorous community action

**Source**: Bolt Beranek and Neuman, Inc., *Fundamentals and Abatement of Highway Traffic Noise*, Report No. PB-222-703. Prepared for Federal Highway Administration, June 1973.




#### **Noise Assessment Procedure**

- Determine sensitive receptor locations within the adjacent study area where the maximum construction noise levels would be likely to occur
- Measure the existing ambient noise levels at the selected receptor locations
- Determine worst case Leq(1) at noise receptors due to construction activities
- Use appropriate mathematical models to predict construction noise levels
- Determine noise impacts using the CEQR criteria
- Provide mitigation measures if any noise impacts would occur



### **Construction Noise Analysis Results**



**Atlantic Yards Arena** 




### **Construction Noise Analysis Results**



**First Avenue Properties** 



### **Construction Noise Analysis Results**



Columbia Manhattanville



#### **Findings**

- Construction noise is one of significant environmental concerns
- Noise impacts would be unavoidable based on the CEQR criteria even with mitigation measures
- Change of 3 dBA or lower is Barely perceptible
- Change of 5 dBA or higher is readily noticeable
- Compared to Federal and State noise criteria, the CEQR noise impact criteria is quite stringent
- Change of 5 dBA represents a conservative impact threshold
- A proposed construction noise criterion Baseline + 5 dBA